AkzoNobel

SAFETY DATA SHEET

Autowave Optima MM V727 Violet (Red) Transparent

Section 1. Identification

GHS product identifier : Autowave Optima MM V727 Violet (Red) Transparent

SDS code : 055494

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use

Uses advised against

consumer use

Supplier's details

Akzo Nobel Coatings, Inc.

1845 Maxwell

Troy, MI, 48084

Ush

Akzo Nobel Coatings Ltd.

110 Woodbine Downs Blvd.

Unit #4 Etobicoke, Ontario

Canada M9W 5S6

USA Canada M9W 5S6 (800) 618-1010 +1 (800) 618-1010

Emergency telephone number (with hours of operation)

: CHEMTREC +1 (800) 424-9300 (Inside the US)

CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : SKIN SENSITISATION - Category 1 substance or mixture : CARCINOGENICITY - Category 2

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary statements

Date of issue/Date of revision : 6/19/2025 Version : 2

 Date of previous issue
 : 3/5/2025
 1/15

Autowave Optima MM V727 Violet (Red) Transparent

Section 2. Hazards identification

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapour. Contaminated work clothing must not be allowed

out of the workplace.

Response : IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing

before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs:

Get medical advice or attention.

Store locked up. Storage

Disposal : Dispose of contents and container in accordance with all local, regional, national or

international regulations.

Hazards not otherwise

classified

Prevention

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

Ingredient name	%	CAS number
2-butoxyethanol	<10	111-76-2
1-methoxy-2-propanol	≤5	107-98-2
triisobutyl phosphate	≤1	126-71-6
2-ethylhexyl acrylate	≤0.3	103-11-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

> not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may

need to be kept under medical surveillance for 48 hours.

Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Date of issue/Date of revision Version : 2 : 6/19/2025

2/15 Date of previous issue : 3/5/2025

Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

> be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

Date of issue/Date of revision Version : 2 : 6/19/2025 3/15

Date of previous issue : 3/5/2025

Section 5. Firefighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapour, spray or mist. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision Version : 2 : 6/19/2025 4/15 Date of previous issue : 3/5/2025

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2-butoxyethanol	ACGIH TLV (United States, 1/2022).
-	TWA: 20 ppm 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	Absorbed through skin.
	TWA: 25 ppm 8 hours.
	TWA: 120 mg/m³ 8 hours.
	NIOSH REL (United States, 10/2020).
	Absorbed through skin.
	TWA: 5 ppm 10 hours.
	TWA: 24 mg/m³ 10 hours.
	OSHA PEL (United States, 5/2018).
	Absorbed through skin.
	TWA: 50 ppm 8 hours.
	TWA: 240 mg/m³ 8 hours.
1-methoxy-2-propanol	ACGIH TLV (United States, 1/2022).
	STEL: 369 mg/m³ 15 minutes.
	STEL: 100 ppm 15 minutes.
	TWA: 184 mg/m³ 8 hours.
	TWA: 50 ppm 8 hours.
	NIOSH REL (United States, 10/2020).
	STEL: 540 mg/m³ 15 minutes.
	STEL: 150 ppm 15 minutes.
	TWA: 360 mg/m³ 10 hours.
	TWA: 100 ppm 10 hours.
	OSHA PEL 1989 (United States, 3/1989).
	STEL: 540 mg/m³ 15 minutes.
	STEL: 150 ppm 15 minutes.
	TWA: 360 mg/m ³ 8 hours.
	TWA: 100 ppm 8 hours.
triisobutyl phosphate	None.
2-ethylhexyl acrylate	None.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Date of issue/Date of revision	: 6/19/2025	Version	:2	
Date of previous issue	: 3/5/2025	5/15		

Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/ or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

: Liquid. **Physical state** : Violet. Colour

Odour : Not available. **Odour threshold** : Not available.

pН : 8 [Conc. (% w/w): 100%] [DIN EN 1262]

Melting point/freezing point Boiling point, initial boiling point, and boiling range

: Not available. : 100°C (212°F)

Flash point : Not available. **Flammability** : Not available. Lower and upper explosion

limit

Date of issue/Date of revision Version : 2 : 6/19/2025

: Not applicable.

6/15 Date of previous issue : 3/5/2025

Section 9. Physical and chemical properties and safety characteristics

Vapour pressure

	Vapour Pressure at 20°C			Va	oour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
1-methoxy-2-propanol	8.5	1.1				
2-butoxyethanol	0.75	0.1				

Relative vapour density : Not available.

Relative density : 1.033 [ISO 8130-2/-3]

Solubility(ies)

Not available.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-butoxyethanol	230	446	DIN 51794
1-methoxy-2-propanol	270	518	
5,12-dihydro-2,9-dimethylquino[2,3-b]acridine-7,14-dione	280	536	VDI 2263

Decomposition temperature: Not available.

: Kinematic (room temperature): 484 mm²/s (484 cSt) [DIN EN ISO 3219] **Viscosity**

Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]

(****To be Translated***)

Weight Volatiles

: **7**5.25% (w/w)

(****To be Translated****)

Volume Volatiles

78.71 %(v/v)

(****To be Translated****)

: 24.75 %(w/w)

Weight Solids

(****To be Translated****)

: 21.29 %(v/v)

: 2.8

: 0

Volume Solids

(*****To Be Translated****)

lbs/gal

337 g/l minus water and exempt solvents

Regulatory VOC

VOC Actual

: 1.0 lbs/gal 1/14 g/l

Particle characteristics

Median particle size : Not applicable.

Percentage of particles

with aerodynamic diameter

≤ 10 µm

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

7/15

Date of issue/Date of revision : 6/19/2025 Version : 2

Date of previous issue : 3/5/2025

Section 10. Stability and reactivity

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Gas.	Mouse	700 ppm	7 hours
-	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapour	Mouse	3380 mg/m ³	7 hours
	LC50 Inhalation Vapour	Rat	2900 mg/m ³	7 hours
	LD50 Dermal	Guinea pig	230 uL/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Mouse	536 mg/kg	_
	LD50 Intraperitoneal	Rabbit	220 mg/kg	_
	LD50 Intraperitoneal	Rat	220 mg/kg	_
	LD50 Intravenous	Mouse	1130 mg/kg	_
	LD50 Intravenous	Rabbit	252 mg/kg	_
	LD50 Intravenous	Rat	307 mg/kg	_
	LD50 Oral	Guinea pig	1200 mg/kg	_
	LD50 Oral	Mouse	1230 mg/kg	_
	LD50 Oral	Mouse	1167 mg/kg	_
	LD50 Oral	Rabbit	300 mg/kg	_
	LD50 Oral	Rabbit	320 mg/kg	_
	LD50 Oral	Rat	917 mg/kg	_
	LD50 Oral	Rat	250 mg/kg	_
	LD50 Crai	Mouse	1050 mg/kg	_
	unreported	Wodsc	1000 mg/kg	
	LD50 Route of exposure	Rat	917 mg/kg	_
	unreported	INat	917 mg/kg	-
1-methoxy-2-propanol	LC50 Inhalation Gas.	Rat	10000 ppm	5 hours
1-methoxy-z-propanor	LD50 Dermal	Rabbit	13 g/kg	3 flours
	LD50 Definal	Rat	3720 mg/kg	_
	LD50 Intrapentoneal	Mouse	5300 mg/kg	-
	LD50 Intravenous	Rabbit	1200 mg/kg	-
	LD50 Intravenous	Rat		-
	LD50 Intraverious	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	4200 mg/kg 11700 mg/kg	-
	LD50 Oral	Mouse Rabbit		-
			5700 mg/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
	LD50 Subcutaneous	Rabbit	5 g/kg	-
Anii a a baashada a baa a a baasa	LD50 Subcutaneous	Rat	7800 mg/kg	-
triisobutyl phosphate	LD50 Oral	Rat	>5 g/kg	-
2-ethylhexyl acrylate	LD50 Dermal	Rabbit	8480 uL/kg	-
	LD50 Intraperitoneal	Mouse	1326 mg/kg	-
	LD50 Intraperitoneal	Rat	1670 mg/kg	-
	LD50 Oral	Mouse	4400 mg/kg	-
	LD50 Oral	Mouse	4400 mg/kg	-
	LD50 Oral	Rat	6700 mg/kg	-
	LD50 Oral	Rat	6500 uL/kg	-

 Date of issue/Date of revision
 : 6/19/2025
 Version
 : 2

 Date of previous issue
 : 3/5/2025
 8/15

Section 11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
•				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
triisobutyl phosphate	Eyes - Moderate irritant	Rabbit	-	100 UI	-
	Skin - Moderate irritant	Rabbit	-	500 UI	-
2-ethylhexyl acrylate	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Eyes - Severe irritant	Rabbit	-	5 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Skin - Severe irritant	Rabbit	-	24 hours 10	-
				mg	

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
2-butoxyethanol	-	3	-
2-ethylhexyl acrylate	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

	exposure	
Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
		Category 3 -

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

 Date of issue/Date of revision
 : 6/19/2025
 Version
 : 2

 Date of previous issue
 : 3/5/2025
 9/15
 ...

Section 11. Toxicological information

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data. **Inhalation** : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Product as-supplied 2-butoxyethanol	17230.9	N/A	N/A	43.1	N/A
	1200	N/A	N/A	3	N/A

Date of issue/Date of revision : 6/19/2025 Version : 2

 Date of previous issue
 :3/5/2025

 10/15

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 800000 μg/l Marine water Acute LC50 1490000 μg/l Fresh water	Daphnia - Daphnia magna Crustaceans - Crangon crangon Fish - Lepomis macrochirus Fish - Menidia beryllina	48 hours 48 hours 96 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	low
1-methoxy-2-propanol	<1	-	low
2-ethylhexyl acrylate	4.64	-	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (benzene)	-	-	-	-

Date of issue/Date of revision Version : 2 : 6/19/2025 Date of previous issue : 3/5/2025 11/15

Section 14. Transport information

Transport hazard class(es)	9	-	-	-	-
Packing group	III	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Additional information

DOT Classification

: Reportable quantity 49110.3 lbs / 22296.1 kg [5701.8 gal / 21583.8 L]. The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 final significant new use rules: No products found.

TSCA 5(e) substance consent order: No products found.

TSCA 8(a) PAIR: triisobutyl phosphate; n-butyl methacrylate; mequinol

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 307: benzene

Clean Water Act (CWA) 311: benzene; methyl methacrylate

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals (Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

Date of issue/Date of revision : 6/19/2025 Version : 2 Date of previous issue : 3/5/2025 12/15

Section 15. Regulatory information

SARA 311/312

Classification : SKIN SENSITISATION - Category 1

CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
2-butoxyethanol	<10	FLAMMABLE LIQUIDS - Category 4
		ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (inhalation) - Category 3
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
1-methoxy-2-propanol	≤5	FLAMMABLE LIQUIDS - Category 3
		SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE
		(Narcotic effects) - Category 3
triisobutyl phosphate	≤1	SKIN SENSITISATION - Category 1
2-ethylhexyl acrylate	≤0.3	FLAMMABLE LIQUIDS - Category 4
		SKIN IRRITATION - Category 2
		SKIN SENSITISATION - Category 1
		CARCINOGENICITY - Category 2
		SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE
		(Respiratory tract irritation) - Category 3

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	2-butoxyethanol	111-76-2	<10
Supplier notification	2-butoxyethanol	111-76-2	<10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: 2-BUTOXYETHANOL; PROPYLENE GLYCOL

METHYL ETHER

New York : None of the components are listed.

: The following components are listed: 2-BUTOXY ETHANOL; PROPYLENE GLYCOL **New Jersey**

MONOMETHYL ETHER

Pennsylvania : The following components are listed: ETHANOL, 2-BUTOXY-; 2-PROPANOL,

1-METHOXY-

California Prop. 65

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
2-ethylhexyl acrylate benzene	- Yes.	- Yes.	Cancer Cancer, Developmental, Reproductive male

Inventory list

Australia : All components are listed or exempted. Canada : At least one component is not listed.

Date of issue/Date of revision : 6/19/2025 Version : 2 13/15 Date of previous issue : 3/5/2025

Section 15. Regulatory information

China : At least one component is not listed.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): At least one component is not listed.

Japan inventory (ISHL): Not determined.

New Zealand : At least one component is not listed.

Philippines : At least one component is not listed.

Republic of Korea : At least one component is not listed.

Taiwan : At least one component is not listed.

Thailand: Not determined.

Turkey : At least one component is not listed.
United States : All components are active or exempted.

Viet Nam : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Classification	Justification	
3 7	Calculation method Calculation method	

History

Date of printing : 6/20/2025 Date of issue/ Date of : 6/19/2025

revision

Date of previous issue : 3/5/2025

Version : 2

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

 Date of issue/Date of revision
 : 6/19/2025
 Version
 : 2

 Date of previous issue
 : 3/5/2025
 14/15

Autowave Optima MM V727 Violet (Red) Transparent

Section 16. Other information

UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws. Any person using this product must determine for themselves, by preliminary tests or otherwise, the suitability of this product for their purposes. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. The application, use and processing of AkzoNobel's products and the products manufactured by Buyer on the basis of AkzoNobel's technical advice are beyond AkzoNobel's control and, therefore, entirely Buyer's own responsibility. AkzoNobel makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

IA_413

Date of issue/Date of revision: 6/19/2025Version: 2Date of previous issue: 3/5/202515/15